



Certificate of conformity of the factory production control

Reg.-Nr. 1075-CPR-Z420-15/18

In compliance with Regulation 305/2011/EU of the European Parliament and the council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Wood-based panels for use in construction Type Softwood Plywood (see Annex 1)

manufactured by Producer

Ilim Timber, LLC
Maly prospect, V.O., 54
building 2, liter A1
199178, Saint-Petersburg
Russia

at manufacturing plant

Bratsk Branch of Ilim Timber, LLC
BLPK Industrial site
665718, Bratsk, Irkutsk region
Russia


This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 13986:2004+A1:2015

under **system 2+** are applied and that the factory production control fulfils all the prescribed requirements set out above.

This certificate was first issued on 18th of August 2015 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

Bremen, 2nd of July 2018


(Dipl.-Ing. Axel Meyer)
Chief of authorised Certification Body of MPA Bremen



The validity of the certificate is confirmed by the publication on the official website of the MPA Bremen: <http://www.mpa-bremen.de>.



Durch die DAKKS nach DIN EN ISO/IEC 17065 akkreditierte
Produktzertifizierungsstelle.
Die Akkreditierung gilt für die in der Urkunde aufgeführten
Zertifizierungsverfahren.



Notifizierte Stelle - Notified Body NB 1075



ANNEX 1 FOR

Certificate of conformity of the factory production control

Reg.-Nr. 1075-CPR-Z420-15/18

Product:

Wood-based panels for use in construction Type Softwood Plywood

for internal use in humid conditions (uncoated), EN 636-2
 as structural components

Nominal thickness [mm]	No. of layers	Class of bending strength		Class of modulus of elasticity	
		along the grain	across the grain	along the grain	across the grain
6,5	3	F 20	F 5	E 35	E 5
9	3	F 35	F 5	E 80	E 5
9	5	F 25	F 10	E 70	E 15
12	5	F 20	F 10	E 50	E 30
15	7	F 20	F 10	E 50	E 25
18/19	9	F 20	F 10	E 50	E 25
21	9	F 20	F 15	E 50	E 30
21	11	F 15	F 10	E 35	E 25
24	11	F 20	F 10	E 50	E 30
27	11	F 15	F 15	E 35	E 35
30	13	F 15	F 10	E 40	E 30